

Hestia doors - Technical specifications



Florence L Series (FLL)



Item	Specifications	Materials & notes
Door Frame		
Door frame	37*100 / 37*125mm	laminated solid wood
Frame expansion plate	15mm	mdf board
Architrave trim	70*18mm (vertical & horizontal)	type XA/XB/XC in laminated wood
Frame finish	0.3mm wood veneers or water-based paints	coated in chosen finishings
Hinge	concealed hinge 2 per set	if opening h>2200mm or w>1000mm 3 per set
Rubber gasket	12*6mm	Clear, brown or black (non-elastic)
Frame adjustability	20mm	
Wall thickness	minimum 80mm	
Door leaf		
Standard type	42mm with decorative panel S-type	-perimetric structure in laminated wood -covered in 5mm mdf board -panel in 25mm mdf board -6 panel designs: LA/LB/LC/LD/LE/LF
Finish	in wood veneered or water-based paints coated with chosen finishings	
Other available type	Flush panel, glazed, line design or patterned veneer	G1-G11, H1-H5, E1-E5
Leaf standard size	2032 x 813mm	
Leaf width calculation	Finished opening width - 74mm	
Leaf height calculation	Finished opening height - 43mm	
Maximum leaf height	2300mm	
Maximum leaf width	1000mm	
Opening requirements		
Wall buttress	>50mm on sides and top	
Floor joint	21mm	from inner edge of opening toward centre
Supply		
Lead time	10 - 12 weeks	from acceptance of quote and confirmation of sizes
Installation	R 400.00 per set	
Guarantee	2-years	against manufacturer's faults & defects