Urbino - Brief specifications (UB)			URBINO interior door system
unit = mm	Vanguard	Avant-garde	Crystalline
			0-
Door leaf structure & dimensions			
Stile & rail:	3mm aluminium alloy channels		
In-fill:	23.5mm aluminium alloy honeycomb core		Safety glass
Cladding:	5mm medium density fiberboard (MDF)		n/a
Surface finishes:	Laminate / Aluminate / wood veneer		clear / sandblast / mirror
Edge band:	Aluminium	Aluminium	Aluminium
Ironmongery:	Factory-fitted	Factory-fitted	Factory-fitted
Standard size:	2032 x 813mm	2032 x 813mm	2032 x 800mm
Thickness:	40mm	40mm	40mm
Maximum height:	2320mm	2320mm	2200mm
Maximum width:	830-850mm	830-850mm	800mm
Door frame structure & dimensions			
Name:	Aluminium alloy (UB002)	Aluminium alloy (UB003)	Aluminium alloy (UB009)
Type:	inter-lock	inter-lock	inter-lock
Architrave:	Integrated	Integrated	Integrated
Surface finishes:	Aluminium with inlay	Satin aluminium	Satin aluminium
Rubber gasket:	Grey (non-elastic)	Clear (non-elastic)	Clear (non-elastic)
Hinges:	Stainless steel	Stainless steel	Stainless steel
Architrave width:	72mm	76mm	72mm
Adjustability:	20mm	20mm	20mm
Fit wall thickness:	120-290mm	120-290mm	120-290mm
Opening dimension calcula	ition		
Internal width:	Leaf width + (60 ~ 80)mm		
Internal height:	Leaf height + (50~60)mm + floor thickness		
Wall buttress width:	All openings must have 40mm wall buttresses on both sides		
Variation allowance:	3 to 5mm		
Supply			
Lead time:	8 to 12 weeks from order confirmation		
Installation:	Will be carreid out by our approved/trained installers		
	4.175.57		

Warranty:



2007-12-7 Urbino brief specs

1 year