

Urbino - Brief specifications (KF)



Door leaf structure & dimensions

Stile & rail:	3mm aluminium alloy channels
In-fill:	23.5mm aluminium alloy honeycomb core
Cladding:	5mm medium density fiberboard (MDF)
Surface finishes:	Laminate / Aluminate / wood veneer
Edge band:	Aluminium
Ironmongery:	Factory-fitted
Standard size:	2032 x 813mm
Thickness:	40mm
Maximum height:	2320mm
Maximum width:	850mm

Door frame structure & dimensions

Name:	Composite aluminium (KF)
Type:	Solid wood sub-frame
Architrave:	Yes
Surface finishes:	Laminate on aluminium
Rubber gasket:	Black (non-elastic)
Hinges:	Stainless steel
Architrave width:	70mm
Adjustability:	40mm
Fit wall thickness:	90-290mm

Opening dimension calculation

Internal width:	Leaf width + (90 ~ 100)mm
Internal height:	Leaf height + (60~70)mm + floor thickness
Wall buttress width:	All openings must have 40mm wall buttresses on both sides
Error margin:	3 to 5mm

Supply

Lead time:	8 to 12 weeks from order confirmation
Installation:	Will be carried out by our approved/trained installers
Warranty:	1 year

